## Product data sheet Characteristics

## 1248004

# Thorsman - cavity fixing - TSP 10xM5 - with screw - set of 25



| Main                      |                       |
|---------------------------|-----------------------|
| Range of product          | Thorsman              |
| Product or component type | Cavity fixing         |
| Device short name         | TSP                   |
| Provided equipment        | Screw                 |
| Device application        | 335 mm board material |
| Colour tint               | Blue<br>White         |
| Quantity per set          | Set of 25             |

### Complementary

| Mounting support       | Wall mounted  |  |
|------------------------|---|--|
| Thread type            | M5  |  |
| Screw length           | 65 mm   |  |
| Drilling diameter      | 10 mm   |  |
| Material               | PA (polyamide)<br>Electroplated: steel screw  |  |
| Pratical load capacity | 0.15 kN pull-out load: 2 x 13 mm board 0.4 kN shear: 2 x 13 mm board 0.075 kN pull-out load: 13 mm board 0.25 kN shear: 13 mm board |  |
| Thickness              | 012 mm fixture:[sapce]2 x 13 mm board 025 mm fixture:[sapce]13 mm board   |  |
| Diameter               | 20 mm   |  |
| Length                 | 68 mm   |  |
| Product weight         | 0.0106 kg   |  |

#### Environment

| Environmental characteristic          | Corrosion resistance |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -4080 °C             |

#### Contractual warranty

|        | <u> </u>  |
|--------|-----------|
| Period | 18 months |