

Light fitting BRSB 3x12 LED, 3000 K, opal PMMA cover, 285 mm, IP44, DALI

Code: **BRSB3KO300V1/DALI**

EAN: **8595073767025**



Luminaire properties

Product category:	Surface mounted ceiling- and wall luminaire	Suitable for through-wiring:	Yes
Material housing:	Steel	Color housing:	White
Type of luminaire:	Luminaire with cover	Degree of protection (IP):	IP44
Suitable for emergency lighting:	No		

Light source

Lamp type:	LED	Rated life time L80/B50 (h):	80000
Suitable for number of lamps:	1	Lamp power (W):	14
Effective luminous flux (lm):	1300	Color temperature (K):	3000
Color rendering index CRI:	80-89	With lamp:	Yes

Electical properties

Dimmable:	Yes	Type of dimming:	DALI
Type of control gear:	Electronic ballast-DALI	Protection class:	I
Nominal voltage (V):	220...240	Control gear included:	Yes

Optical system

Optical system:	KO	Light sharing:	Symmetric
Color cover:	White	Light outlet:	Direct
Material cover:	Plastic, opal		

Dimensions

Height/depth (mm):	89	Diameter (mm):	285
Weight (kg):	0,75		

Type of surface:	Matt	Suitable for wall mounting:	Yes
-------------------------	------	------------------------------------	-----