



Description

Article

Part No.: 32 601

EQUES[®] 60Classic

adapter 290 A

for ABB T-max T4, Siemens 3RV1,
connection to the system top

105 x 240

System

60Classic

Product group 05

Untergruppe 36

pack size 1

EAN 4021267326012

catalog page 2015 : 2/16

Classification

eCl@ss 6.1 27370304

eCl@ss 7.1 27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Approvals

Standards

IEC 61439-1:2011

Approvals

UL, Germanischer Lloyd



for UL feeder circuits >250V

Type number: EPC60250-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

CCC approval: no certification required

Product data

Electrical data

Rated current (IEC): 290 A

Rated voltage (IEC) AC: 690 V

Rated current (UL): 250 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 26.1 W.
(The power dissipation for operation with rated current would be 40.8 W.)

rated isolation voltage U_i (AC): 800 V

Rated surge voltage U_{imp} : 6 kV

max. permitted voltage (IEC) AC: 800 V

max. permitted voltage (IEC) DC: 800 V

short-circuit withstandability: the MCCB gives the short-circuit protection to the adapter

Mechanical data

W x H x D: 105 x 240 x 35

L x W x D: x x

Weight: 122 kg/100

Poles: 3-pole

Material properties

Body:

temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free
