


Steel cable trays

Hot-dip galvanized

Corrosion class C3, C4

Cable trays, perforated

Type	Dimensions A/B/C mm		Weight kg/100 m	EAN code	Ref. No.
Cable tray W3					
Perforated cable tray for indoor or outdoor industrial applications. System height 40 mm. Provided with holes Ø 5.8 mm at the tray end to be used for fixation of joints. Oval holes along the lateral sides of the tray can be used for mounting of accessories. Material: Steel, hot-dip galvanized.					
W3/40-50	40/50/3000		110	7321677354009	735400
W3/40-70	40/70/3000		120	7321677354016	735401
W3/40-100	40/100/3000		156	7321677354023	735402
W3/40-150	40/150/3000		170	7321677354030	735403
W3/40-200	40/200/3000		220	7321677354047	735404
W3/40-300	40/300/3000		350	7321677354054	735405
W3/40-400	40/400/3000		453	7321677354061	735406
W3/40-500	40/500/3000		620	7321677354078	735407
W3/40-600	40/600/3000		723	7321677354085	735408




Installation tray W4

Perforated installation tray for indoor or outdoor industrial applications. To be used when leading cables down from a cable ladder to machine cabinets, etc. Provided with holes Ø 3.5 mm in the bottom segment of the tray for the clamping of cables with plate screws.

Material: Steel, hot-dip galvanized.

W4-50	15/50/1960 15/50/3000	57	7321677366132 7321677359776	736613 735977
W4-75	15/75/1960 15/75/3000	76	7321677366149 7321677359783	736614 735978
W4-100	15/100/1960 15/100/3000	93	7321677366156 7321677359790	736615 735979
W4-150	15/150/1960 15/150/3000	125	7321677366163 7321677359806	736616 735980
W4-200	15/200/1960 15/200/3000	195	7321677366170 7321677359813	736617 735981
W4-250	15/250/1960 15/250/3000	228	7321677366187 7321677359820	736618 735982
W4-300	15/300/1960	238	7321677366194	736619
W4-400	15/400/1960	313	7321677366200	736620



Lighting trunking

Lighting trunking W70-40

Cable tray with bottom perforation for indoor or outdoor industrial applications. System height 22 mm, length 2995 mm. The oval hole pattern at the base of the tray can be used for mounting of lighting fixtures.

Material: Steel, hot-dip galvanized.

W70-40	22/40/2995	113	7321677900671	790067
--------	------------	-----	---------------	--------



Lighting trunking W70-70, -100

Cable tray with bottom perforation for indoor or outdoor industrial applications. System height 40 mm, length 3000 mm. Oval holes 9x5.8 mm on the lateral sides of the tray end can be used for fixation of joints. The oval hole pattern at the base of the tray can be used for mounting of lighting fixtures. On every 500 mm a 45° turned oval hole is placed to easily guide fast connectors into the tray.

Material: Steel, hot-dip galvanized.

W70-70	40/70/3000	293	3606480464812	CSU794528
W70-100	40/100/3000	346	3606480464829	CSU794529

