

Cable Ties Polyamide 6.6 standard T30R



T-Series in PA66 black, Article number: 111-03011

- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.

RoHS ✓

HF ✓



Base Data

Application Tool	MK3SP, MK3PNSP2, MK7P, EVO7, MK20
Colour	Black (BK)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T30R PA66 BK 100
Product Family	T-Series in PA66 black
Product Group	Cable Ties Polyamide 6.6 standard
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T30R.NB3P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	35.0 mm
Bundle Ø max. (imperial)	1.38 "
Bundle Ø min.	1.5 mm
Bundle Ø min. (imperial)	.06 "
Length (L)	150 mm
Length (L) (imperial)	5.9 "
Min. Tensile Strength (lbs)	30 lbs
Min. Tensile Strength (N)	135 N
Width (W)	3.5 mm
Width (W) (imperial)	.14 "

Logistic and Packaging

EAN / GTIN	5022660018770
Pack Cont.	100
Quantity per	Bag
Weight	0.7 kg

Material and Specifications

Flammability	UL94 V2
Halogenfree	Yes
Material	PA66
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)
Specification	UL ZODZ2.E64963, DIN 30015955, BV 03856/H0 BV, Det Norske Veritas