


**LK-Series, Article number: 111-00127**

- Wide range of materials and sizes
- Inside serrated ties for a strong hold around bundles
- High tensile strength with very low insertion force
- Simple and quick to install
- Easy application either manually or with a processing tool

For routing, bundling and securing of cables, pipes and hoses.



Catalogue page (February 2014)



All catalogue pages

**Base Data**

|                                           |                                                                        |
|-------------------------------------------|------------------------------------------------------------------------|
| Application Tool                          | MK3SP, MK3PNSP2, MK7P, EVO7, MK7HT, MK20, MK6, MK6PN, MK9, MK9HT, MK21 |
| Colour                                    | Black (BK)                                                             |
| Fixation Method (FF)                      | None                                                                   |
| Identification Plate Position             | none                                                                   |
| Manufacturer Short Description calculated | LK2A PA66HIR(S) BK 100                                                 |
| Product Family                            | LK-Series                                                              |
| Product Group                             | Cable Ties in-between size to T-Series                                 |
| Releasable Closure (Yes/No)               | No                                                                     |
| Tie Closure                               | plastic pawl                                                           |
| Type                                      | LK2A.SB929                                                             |
| Variant                                   | Inside Serrated                                                        |

**Product Dimensions**

|                          |         |
|--------------------------|---------|
| Bundle Ø max.            | 73.0 mm |
| Bundle Ø min.            | 5.0 mm  |
| Length (L)               | 270 mm  |
| Min.Tensile Strength (N) | 225 N   |
| Width (W)                | 4.6 mm  |

**Logistic and Packaging**

|              |               |
|--------------|---------------|
| EAN / GTIN   | 5022660309564 |
| Pack Cont.   | 100           |
| Quantity per | Bag           |

**Material and Specifications**

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| ELV compliant Dir. Art. 4 (2) | YES                                                  |
| Flammability                  | UL94 HB                                              |
| Halogenfree                   | Yes                                                  |
| Material                      | Polyamide 6.6 High Imp. Mod. scan black (PA66HIR(S)) |
| Material                      | PA66HIR(S)                                           |
| Operating Temperature         | -40 °C to +80 °C, (+105 °C, 500 h)                   |
| REACH compliant Regu. Art. 33 | YES                                                  |
| Specification                 | BV                                                   |