



Cable Ties for higher impact resistant Polyamide 6.6 ScanBlack T50L



T-Series in PA66HIR(S), Article number: 111-05441

- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.



Catalogue page (February 2014)



All catalogue pages

Base Data

Application Tool	MK3SP, MK3PNSP2, MK7P, EVO7, MK7HT, MK20, MK6, MK6PN, MK9, MK9HT, MK21
Colour	Black (BK)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T50L PA66HIR(S) BK 100
Product Family	T-Series in PA66HIR(S)
Product Group	Cable Ties for higher impact resistant Polyamide 6.6 ScanBlack
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T50L.S13P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	110 mm
Bundle Ø min.	1.5 mm
Length (L)	390 mm
Min.Tensile Strength (N)	225 N
Width (W)	4.6 mm
Width (W) (imperial)	0.18 "

Logistic and Packaging

EAN / GTIN	5022660322549
Pack Cont.	100
Quantity per	Bag

Material and Specifications

ELV compliant Dir. Art. 4 (2)	YES
Flammability	UL94 HB
Halogenfree	Yes
Material	PA66HIR(S)
Material	Polyamide 6.6 High Imp. Mod. scan black (PA66HIR(S))
Operating Temperature	-40 °C to +80 °C, (+105 °C, 500 h)
REACH compliant Regu. Art. 33	YES