

Cable Ties Polyamide 6.6 standard T30L

**T-Series in PA66 black, Article number: 111-03410**

- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.



Catalogue page (February 2014)



All catalogue pages

Base Data

Application Tool	MK3SP, MK3PNSP2, MK7P, EVO7, MK20
Colour	Black (BK)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T30L PA66 BK 100
Product Family	T-Series in PA66 black
Product Group	Cable Ties Polyamide 6.6 standard
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T30L.NB3P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	50.0 mm
Bundle Ø max. (imperial)	1.97 "
Bundle Ø min.	1.5 mm
Bundle Ø min. (imperial)	.059 "
Length (L)	198 mm
Length (L) (imperial)	7.48 "
Min. Tensile Strength (lbs)	30 lbs
Min.Tensile Strength (N)	135 N
Thickness (T)	1.2 mm
Width (W)	3.5 mm
Width (W) (imperial)	.138 "

Logistic and Packaging

Carton Quantity	8000 pcs.
EAN / GTIN	5022660018848
Pack Cont.	100
Quantity of Europallet	180000 pcs.
Quantity per	pieces
Weight	0.75 kg

Material and Specifications

ELV compliant Dir. Art. 4 (2)	YES
Flammability	UL94 V2
Halogenfree	Yes
Material	PA66
Material	Polyamide 6.6 (PA66)

Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)
REACH compliant Regu. Art. 33	YES
Specification	UL ZODZ2.E64963, DIN 30015955, BV 03856/H0 BV, Det Norske Veritas