## O-range ECON® 2 / 3 / 4 - gang junction boxes



**LUFTDICHT** 

## O-range ECON® 3 Three-gang junction box

- · Air-tight version with sealing membrane
- · Toolless cable and conduit entries
- · Integrated cable retention for the NYM cable, self-locking of the conduits
- Standardised separation of the individual installation openings by means of an insertable separator
- · combinable with all O-range® programme applications

Order number:	9253-22
EAN:	4013456550902
For panel thickness	7 - 40 mm
Depth	48 mm
Cut hole Ø	3 x 68 mm
Centre distance	71 mm
Number of installation device openings	3
Number of bridges	1
Device screws +/-	6
Conduit entries up to Ø 20 mm	6
Conduit entries up to Ø 25 mm	2
Cable entries 3 x 1.5 mm <sup>2</sup>	2
Cable entries 3 x 2.5 mm <sup>2</sup> or 5 x 1.5 mm <sup>2</sup>	2
Packaging inner/dispatch	5/50
Price group	180

With the new O-range ECON® 2 / 3 / 4 - gang junction boxes, KAISER offers the perfect basis and especially easy processing for the fitting of all standard installation accessories in multiple combinations. Thanks to their large installation opening without a central separation, it is easy to wire multiple devices together and even makes possible the use of pre-wired installation accessories. If different electrical circuits – e. g. for supply and communication connections – are used within a combination, the individual accessory installation spaces can be separated easily and in a standardised way.

- · Easy installation of pre-wired accessories without spatial separation
- · Maximum flexibility when fixing accessories, generous tolerance compensation
- Standardised separation of the individual installation openings by means of an insertable separator
- · Complete mounting and installation with just one screw drive
- · combinable with all O-range® programme applications

O-range ECON<sup>®</sup> tight













