

- Schuko power socket 33°
 - Rastec 45 2-pole 16 A / 250 V
 - Spring-loaded terminals
 - Dimensions of single module:
45 x 45 mm
 - Dimensions of double module:
45 x 90 mm
 - Dimensions of triple module:
45 x 135 mm
- Available colours**
- RAL 9010, pure white
 - RAL 2004, pure orange
 - RAL 6029, mint green



ESR1339010

Schuko power socket 33° Rastec 45, single

Designation	PU	Order no.
Schuko power socket single Rastec 33G rw	20	ESR1339010
Schuko power socket single Rastec 33G ro	20	ESR1332004
Schuko power socket single Rastec 33G mg	20	ESR1336029



ESR2339010

Schuko power socket 33° Rastec 45, double


Designation	PU	Order no.
Schuko power socket double Rastec 33G rw	1	ESR2339010
Schuko power socket double Rastec 20G ro	1	ESR2332004
Schuko power socket double Rastec 33G mg	1	ESR2336029



ESR3339010

Schuko power socket 33° Rastec 45, triple

Designation	PU	Order no.
Schuko power socket triple Rastec 33G rw	1	ESR3339010
Schuko power socket triple Rastec 33G ro	1	ESR3332004
Schuko power socket triple Rastec 33G mg	1	ESR3336029



EUS315

Overvoltage fine protection

Properties:

- The overvoltage protection conductor is designed for line-side fine protection of electronic equipment and is provided, in particular, for installation in device casings, with acoustic fault signalling.
- EUS315 - Overvoltage protection module with 3 connecting lines, each 1.5 mm², for connection of a single or multiple socket
- EUS615 - Overvoltage protection module with 6 connecting lines, each 1.5 mm², for through wiring of several single sockets or multiple sockets

Designation	PU	Order no.
Fine protection with 3 connections, each 1.5 mm ²	1	EUS315
Fine protection with 6 connections, each 1.5 mm ²	1	EUS615