



### Main

|                               |                          |
|-------------------------------|--------------------------|
| Range of product              | Thorsman                 |
| Product or component type     | Wall plug                |
| Device short name             | TP                       |
| Provided equipment            | Without screw            |
| Device application            | Lightweight installation |
| Colour tint                   | White                    |
| Quantity per set              | Set of 100               |
| Sale per indivisible quantity | 10                       |

### Complementary

|                         |  |
|-------------------------|--|
| Drilling diameter       | 5.5 mm brick<br>5.5 mm concrete  |
| Drilling depth          | >= 20 mm   |
| Screw diameter          | 3.5...5 mm   |
| Material                | PEHD (polyethylene high density)   |
| Practical load capacity | 0.15 kN pull-out load: solid brick<br>0.3 kN shear: solid brick<br>0.15 kN pull-out load: concrete<br>0.4 kN shear: concrete |
| Diameter                | 5.5 mm   |
| Length                  | 16.5 mm  |
| Product weight          | 0.0004 kg  |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -50...80 °C |
|---------------------------------------|-------------|

### Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|