

| Art.-No.  | VE | PG  | EAN |
|-----------|----|-----|-----|
| 822101035 | 1  | 116 |     |

INFRAcontrol PR-AP 360° IP20 INFRAcontrol presence detector, color white, On-wall-ceiling mounting, protection degree IP20, Detection angle 360°, Detection range 16m, recommend mounting high 2,5m, swichting time 5 Sec. - 15 min., light treshold adjustable 10 - 500 Lux, 3-wire device for ohmic and inductive Load, Power supply 230 VAC, 50 Hz, rated current 16A, Incandescent max. 2.000 W, Fluorescent max. 2.000 W, LED-Loads suitable. Energy saving lamps suitable. Protection class II. IR remote control.

| Technical data                    |                           | 822101035 |
|-----------------------------------|---------------------------|-----------|
| Model                             | Presence detector         |           |
| Mounting method                   | Surface mounted (plaster) |           |
| Colour                            | White                     |           |
| Degree of protection (IP)         | IP20                      |           |
| Optimum mounting height           | 2.5m                      |           |
| Max. transmission range frontally | 16m                       |           |
| Frequency                         | 50Hz                      |           |
| Nominal voltage                   | 230V                      |           |
| Detection angle horizontal        | 360°                      |           |
| Response value luminosity         | 10-500lx                  |           |
| Max. starting current             | 16A                       |           |

