

ENSTO

CJH33.1203CTT

Hybridskarv

Kod	CJH33.1203CTT
GTIN	6438100346690
E-nummer	0702839
Namn	Hybridskarv
Beskrivning	12 kV Al/Cu 150-240 mm ² 3 ledare med skarvhylsor inkl TT sats Kabelskarv avsedd för PEX-isolerade runda 3-ledarkablar max 12 kV. Kabelskarvarna levereras i kompletta satser med erforderlig kallkrympisolation, mastik, tejp, rengöringsmaterial, kopparnät, samt en yttermantel i värmekrymp. Inklusive skruvskarvhylsor med brytskalle



Återförsäljare

Teknisk specifikation

Others

ETIM Class: EC001169

Cable Features

Insulation material: Plastic
Screen/Shield material: Cu-wire

Dimensions

Isoleringens diam.: ≥ 20 mm
Ledarstorlek 12 kV: Al/Cu 120-240
Längd: 1300 mm
Max. application diam.: 34 ... 34 mm
Nominal cross section: 120 ... 240 mm²
Spiral inner diam.: 50 mm
Yttermantel dia.: ≥ 36 mm

Features

Spänningsklass: 6/10 (12) kV

ETIM

Etim

Connection accessories (included):	Screw connector with shear-off head
Halogen free:	True
Model:	Hybrid-shrink
Nominal cross section conductor:	120 ... 240 mm ²
Number of conductors:	3
Rated voltage U ₀ /U (U _m):	6.35/11 (12) kV
With concentric shielding:	True

Packaging

Standardpaket

Unit:	PCE
Paketstorlek:	1
Depth:	1000 mm
Width:	120 mm
Height:	110 mm
Volume:	13,2 l