

DIGITUS Modular Plug for Round Cable, CAT 6A, shielded

AK-219604**EAN 4016032380627****CAT 6A Modular Plug, 8P8C, shielded for solid wire AWG 22-23**

These modular plugs can be used to establish quick and simple connections.

- Layout performance: CAT 6A, 10GBase-T
- Area of application: Patch cable assembly
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
 - UL certified
- Technical properties:
 - Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.6 µ gold-plated
- Flammability: UL 94V-2
- Physical properties:
 - Insertion force: ≤ 30 N

- Diameter Cu-Conductor: AWG (23/1... 22/1)
- Operating temperature: -40 °C to +80 °C
- Current carrying capacity: 1A -1.5A at 50 °C
- Colour: Transparent
- Model: Plug
- Connection type: Crimp
- Screened: yes
- Category: 6A (IEC)
- Suitable for round cable: yes
- Suitable for flat cable: no
- Suitable for litz wire conductor: no
- Suitable for solid core: yes
- Type of connector: RJ45 8(8)
- AWG-range: 23 ... 22
- Special tool necessary: yes

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3600	14.34	37.00	51.00	33.00	62,271.00
Packaging Unit Inside	100	0.40	23.00	33.00	2.00	1,518.00
Packaging Unit Single	1	0.00	1.00	2.00	0.50	1.00
Net single without Packaging	1	-0.06	1.00	2.00	0.50	1.00

More images: