

Datasheet

Art.No. 92.232.1004.1

Cable assembly GST18I3K1-S 15 10SW

gesis® Connection cable male - free end; length: 1m; type GST18I3; 3-pole; 250 V / 16 A; colour of coding: black with black strain-relief; cable: H05VV-F 3G1,5, colour: black



Art.No.	92.232.1004.1
EAN	4015573318311
Order unit	1 pieces

Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Accessories

Art.No.:	Type:	Description
05.561.3653.0	Cover cap GST18i3VS B WS	Cover piece for female GST18i3, white
05.561.3653.1	Cover cap GST18i3VS B SW	Cover piece for female GST18i3, black
05.564.5353.0	Cover cap GST18i3/4/5 SW	Cover piece 12 pole black for female parts GST18i3-6
05.564.5353.2	Cover cap GST18i3/4/5 WS	Cover piece 12 pole white for female parts GST18i3-6
05.587.3156.0	Locking slide (G)ST18 WS	Locking device for cable to cable connection GST18i3-5, white
05.587.3156.1	Locking slide (G)ST18 SW	Locking device for cable to cable connection GST18i3-5, black
05.594.4250.0	Cover cap ST18/3B + GST18i3 ST WS	
05.594.4253.0	Cover cap ST18/3B + GST18i3 ST WS	
06.561.7853.0	Mounting frame	Mounting frame to snap in GST18i3 connectors into a housing or furniture. Wall thickness: 1,5-2,5 mm. Holds GST18i3 connectors with screw or spring connection and pre- assembled cables.

Drawings

