

Vinyl Electrical Tapes – Premium Vinyl Electrical Tape HTAPE-FLEX1000+ 19x20

HelaTape Flex 1000+, Article number: 710-10602



HelaTape Professional tape ran...



Features

- All-weather, highly flexible, professional grade, self-adhesive vinyl electrical tape
- Excellent performance and durability over wide temperature range from -18°C to +105°C according to CSA C22.2
- VDE approved according to IEC 60454-3-1-7/F-PVCP/90
- Used for insulation, protection, fixing, maintenance, colour coding and more
- Pressure sensitive high quality rubber based adhesive
- Performs continuously at low temperature environment
- Excellent resistance to abrasion, moisture, chemicals, corrosion and UV exposure
- Primary electrical insulation for all wire and cable splices up to 1 kV
- Protective jacketing for low, medium and high voltage splices and repairs
- Flame retardant according to UL 510 Standard
- For indoor and outdoor applications
- Size 19 mm x 20 m is single packed in a plastic can, only 710-10601 comes in a pack of 10 pcs.

Certifications & Approvals



Application

Primary electrical insulation for all wire and cable splices up to 1 kV. Protective jacketing for low, high, and medium voltage splices. Harnessing of wires and cables. Used for indoor and outdoor applications.

HelaTape Flex 1000+ is suitable for following markets and industries



More products in this product group

Vinyl Electrical Tapes – Premium Vinyl Electrical Tape >

Base Data		^
Colour	Black (BK)	
Description Short (BMEcat) (max. 150 characters)	Premium Vinyl Electrical Tape 19mm x 20m black	
Global Part Name	HTAPE-FLEX1000+ 19x20-PVC-BK	
Pack Cont.	1 Reel	
Product Family	HelaTape Flex 1000+	
Product Group	Vinyl Electrical Tapes – Premium Vinyl Electrical Tape	
Quantity per	Reel	
Product Dimensions		^
Length (L)	20 m	

Thickness (T)	0.18 mm
Width (W)	19 mm

Material and Specifications

^

Adhesion to Backing	2.5 N/10 mm
Adhesion to Steel	3.0 N/10 mm
Breaking Strength	35 N/10 mm
Dielectric Strength	45 kV/mm
Elongation at break	300 %
ELV compliant Dir. Art. 4 (2)	YES
Hazardous goods	No
Insulating (Yes/No)	Yes
Material	Polyvinylchloride (PVC)
Operating Temperature - °C	-18 °C to +105 °C
Self extinguishing (Yes/No) ETIM	Yes
Shelf Life	5 years
Specifications	 
Specifications	IEC 60454-3-1-7/F-PVCP/90, UL 510
Suitable for high voltage (Yes/No)	No
UL-File Number	E490183

Logistics and Packaging

v

More Information

^

ETIM 5.0	EC000128
ETIM 6.0	EC000128

Similar products

^

HTAPE-FLEX1000+ 19x6 710-10600 Vinyl Electrical Tapes – Premium Vinyl Electrical Tape	HTAPE-FLEX1000+ 19x20 PACK 710-10601 Vinyl Electrical Tapes – Premium Vinyl Electrical Tape	HTAPE-FLEX1000+ C 19x20 710-10603 Vinyl Electrical Tapes – Premium Vinyl Electrical Tape
HTAPE-FLEX1000+ C 19x20 710-10604 Vinyl Electrical Tapes – Premium Vinyl Electrical Tape	HTAPE-FLEX1000+ C 19x20 710-10605 Vinyl Electrical Tapes – Premium Vinyl Electrical Tape	HTAPE-FLEX1000+ C 19x20 710-10606 Vinyl Electrical Tapes – Premium Vinyl Electrical Tape

Show all v