

BTICINO > Wiring devices > Living Now > IR switches



K4431

Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires – variablethreshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 30 seconds to 10 minutes - 230 Va.c. power supply - 1 module

Technical features

N° of modules	1
Rated power W	460 W
Rated voltage	250 Vac
Rated current	2 A

Documentation

Scheda Tecnica

Technical Data Sheet

Instructions Sheet

<u>Living Now english catalogue</u>

Related products



Covers for 1-module IR switch. For item K4431 - 1 module - white



Covers for 1-module IR switch. For item K4431 - 1 module - black

KG16



Covers for 1-module IR switch. For item K4431 - 1 module - sand

KM16

We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/SCE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/S2/EU: 16 April 2014 ** FED**: Biticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product. Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.