SUIS" WALL-MOUNTED NETWORK CABINET



SU cabinet 12 U high with safety glass door



SINGLE-SECTION CABINET WITH REMOVABLE SIDE PANELS

- Designed for indoor applications.
- Available in 6 usable heights (see reference chart).
- The design of the cabinet is based on bolted frame with safety glass or steel front door and removable rear and side panels.
- Standard version is equipped with two adjustable
 19" mounting angles, a knock-out blanking plate and a brush opening (potential cable entry point).
- The rear and side panels, as well as steel door, are provided with earthing connections.
- Cabinets can be fastened directly to the wall without using any brackets convenient internal access to wallfixing screws.
- Easy change of door opening direction and cable opening layout by rotating by 180°.
- Wide range of supplementary accessories: shelves, drawers, fan kit, power strips etc.
- Cabinet can be equipped with additional rear adjustable 19" mounting angles or mounting profiles.

TECHNICAL DATA

Material

Frame, rear and side panels, mounting angles - sheet steel Door - safety glass or sheet steel

Surface finishing

Frame and mounting angles – Al-Zn coated. Steel door, side panels and rear panel – powder paint, light grey (RAL 7035). All other colour options on request.

Protection degree

IP 20 in accordance with EN 60529 (does not apply to brush cable entries).

SCOPE OF DELIVERY

Frame, bottom plate, top plate, door, 2 side panels, rear panel, 2 mounting angles, brush, template for drilling holes in the wall.




040 ZPAS


SU cabinet

WALL-MOUNTED CABINETS

WALL-MOUNTED NETWORK CABINET








DESIGN


- 1. Bolted frame

- 2. Top plate
 3. Bottom plate
 4. Removable side panel
 5. Removable rear panel
 6. Glass door (steel door

- as anoption)
 7. Mounting angle
 8. Brush strip
 9. Knock-out blanking plate

Supplementary accessories ordered separately:
10. Earthing bar
11. Fan





REFERENCE CHART

De Altere	Width W [mm]	Depth D [mm]	Height H [mm]	Usable height HU [U = 44.45 mm]	Maximum load capacity [kg]	Catalogue number	
Packing method						Cabinet with glass door	Cabinet with steel door
Assembled cabinet	600	400	871	18 U	45	WZ-2733-01-S6-011	WZ-2733-01-M6-011
			737	15 U	37	WZ-2733-01-S5-011	WZ-2733-01-M5-011
			604	12 U	30	WZ-2733-01-S4-011	WZ-2733-01-M4-011
			515	10 U	25	WZ-2733-01-S3-011	WZ-2733-01-M3-011
			337	6 U	15	WZ-2733-01-S2-011	WZ-2733-01-M2-011
			248	4 U	10	WZ-2733-01-S1-011	WZ-2733-01-M1-011
Cabinet in a flat pack for self assembly	600	400	871	18 U	45	WZ-2733-01-F6-011	-
			737	15 U	37	WZ-2733-01-F5-011	-
			604	12 U	30	WZ-2733-01-F4-011	_
			515	10 U	25	WZ-2733-01-F3-011	-
			337	6 U	15	WZ-2733-01-F2-011	-
			248	4 U	10	WZ-2733-01-F1-011	_

WALL-MOUNTED CABINETS SU cabinet		DATA COMMUNICATION SOLUTIONS
	WALL-MOUNTED CABINETS	SU cabinet