

GROUND LIGHTS SPECIFICATION SHEET



GL016 F

1W, 95lm ground light

FEATURES

IK rating	IK09
IP rating	IP68
Colour flexibility	Fixed colour
Walk Over / Drive Over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 50mm
Bathroom zone	0
Efficiency	DRIVER DEPENDANT
Construction Material	Stainless steel (316)
Weight	400g
Maximum ambient temperature	50°C
Electric Class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	350mA			700mA		
				lm	lm/W	lx @ 1m	lm	lm/W	lx @ 1m
GL016 F NW	1W (350mA) 2W (700mA)	4000K	26°	95	95	267	140	70	393
GL016 F WW	1W (350mA) 2W (700mA)	3000K	26°	75	75	210	135	68	379
GL016 F 27	1W (350mA) 2W (700mA)	2700K	26°	70	70	196	120	60	337
GL016 F AMBER	1W (350mA) 2W (700mA)	Amber	26°	-	-	-	-	-	-
GL016 F BLUE	1W (350mA) 2W (700mA)	Blue	26°	20	20	28	20	10	56
GL016 F GREEN	1W (350mA) 2W (700mA)	Green	26°	75	75	211	110	55	310
GL016 F RED	1W (350mA) 2W (700mA)	Red	26°	-	-	-	-	-	-

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10
PLU/700 3-9	N/A	N/A	N/A	N/A	3	9



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- /collingwoodlighting
- /collingwoodlighting
- collingwoodled



GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

- Can be powered by either a 350mA or 700mA low voltage driver, depending on desired light output
- Robust cable for outdoor use
- Shallow depth for easy installation
- marine-grade stainless steel 316

Beam angle: 26°



GROUND LIGHTS SPECIFICATION SHEET


ACCESSORIES


JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/50	Installation tube
WCR 275 BLACK	2-core rubber cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types




COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GL016 F

The GL016 is part of Collingwood's submersible LED range. This mid-sized, stainless steel 1W ground light is ideal for lighting paths, decking and water features. Available in seven ambient LED colours, submersible to 9m and walk over, the GL016 is one of Collingwood's most popular ground lights.