

GROUND LIGHTS SPECIFICATION SHEET



GL019 S T

Up to 2W, 130lm mini threaded ground light

FEATURES

IK rating	IK07
IP rating	IP68
Colour flexibility	Fixed colour
Walk Over / Drive Over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra or -
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 32mm
Bathroom zone	0
Efficiency	DRIVER DEPENDANT
Construction Material	Stainless steel (316)
Weight	140g
Maximum ambient temperature	50°C
Electric Class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	350mA			700mA		
				lm	lm/W	lx @ 1m	lm	lm/W	lx @ 1m
GL019 S T NW	1W (350mA) 2W (700mA)	4000K	12°	90	90	1833	130	65	2648
GL019 S T WW	1W (350mA) 2W (700mA)	3000K	12°	80	80	1629	125	63	2545
GL019 S T 27	1W (350mA) 2W (700mA)	2700K	12°	70	70	1425	115	58	2341
GL019 S T BLUE	1W (350mA) 2W (700mA)	Blue	12°	10	10	204	20	10	407

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10
PLU/700 3-9	N/A	Yes	No	1	3	9

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- /collingwoodlighting
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Can be powered by either a 350mA or 700mA low voltage driver, depending on desired light output

Incorporated thread and nut for secure fitting into panels, walls or ceilings

Shallow depth for easy installation

marine-grade stainless steel 316

Beam angle: 12°

