

WALL LIGHTS SPECIFICATION SHEET



WL013

IP65, 390lm up-down wall light

FEATURES

IK rating	IK04
IP rating	IP65
Colour flexibility	Fixed colour
Input	220-240V 50/60Hz
LED Lifetime	30,000h L70 B10
CRI	>80Ra
SDCM	<6

INSTALLATION INFORMATION

Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
Weight	467g
Maximum ambient temperature	40°C
Electric Class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
--------------	--------	---------	--------	------------	----	------	---------

WL013X30	Black RAL9011	6.5W	3000K	107°/91°	390	60	99
----------	---------------	------	-------	----------	-----	----	----

ACCESSORIES

No accessories required



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- /collingwoodlighting
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty available

FEATURES & BENEFITS

- Ideal for any doorways and entrances
- 107° up and 91° down beam angle
- Straight to mains screw terminals
- Contemporary look and feel with a matt black finish
- IP65 rating making it perfect for all weather conditions
- Comes with a rubber grommet, to stop any water going into the terminals
- Supplied with a bracket at the back for easy installation

Beam angle: 107°/91°

