

GENERAL CATALOGUE

BTICINO > Wiring devices > Livinglight > Dimmer > Universal dimmers



N4411N

Universal pushbutton dimmer (resistive, inductive, capacitive, fluorescent compact and dimmer LEDs) - supply range 100-240 Va.c. - no neutral – 2 modules - white - 240 V.Ac.: Incandescents and hologens 3 - 400 W; Halogens with ferromagnetic transformer 3 - 400 VA; Halogens with electronic transformer 3 - 400 VA; Dimmerable compact fluorescents 3 - 75 W; Dimmerable LED lamps 3 - 75 W. - 100 V.Ac.: Incandescents and hologens 3 - 200 W; Halogens with ferromagnetic transformer - 200 VA; Halogens with electronic transformer 3 - 200 VA; Dimmerable compact fluorescents 3 - 37 W; Dimmerable LED lamps 3 - 37 W.

Technical features

BTicino
3 - 400 VA
3 - 400 W
Livinglight

Documentation

Instruction Sheet

Livinglight Catalogue

Livinglight catalogue - 2 modules version

We, Blicino S.p.A. Viale Borri 231 21100 Varese (Italy), declare that all items listed in Blicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.