

BTICINO > Door entry systems > Accessories for 2 wires system > Accessories















346020

Additional power supply to be used to supply entrance panels and internal units locally. 2 DIN modular enclosure. Power supply 230 Vac at 50-60 Hz. The output provides 27 Vdc continuous low voltage, with maximum current of 600 mA and it is protected on the PRI side (with fuse) against overload and short circuit. It is a SELV double insulation safety device.

Technical features

Brand	BTicino
Standard reference	CEI EN60065
Rated voltage	230 Vac
Rated current	600 mA
Rated power W	3,8 W
N° of modules	2 DIN
Series	Accessories

Documentation

-  [Technical Data Sheet](#)
-  [Instruction Sheet](#)
-  [DWG drawing](#)
-  [Technical guide](#)
-  [Catalogue](#)
-  [Technical guide](#)
-  [Brochure](#)
-  [Catalogue Classe 300](#)
-  [Living Now english catalogue](#)
-  [Catalogue New Classe 100](#)
-  [B2B Catalogue](#)
-  [2 Wires Technical specifications](#)

We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in accordance with the safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certificazioni



Related products



L4669KM1

Sheathed pair made up of 2 flexible wires with unshielded plaited sheath - insulation 300/500 V - co...



308003

Monobloc vandal-resistant 2 wire video pushbutton panel for 12 calls with aluminium finish. The item...



344643

Connected 2 wire / Wi-Fi handsfree video internal unit with inductive loop, 7" Touch Screen LC...



344682

2 WIRES/Wi-Fi handsfree connected video internal unit with inductive loop and 5" colour LCD dis...



308012

Monobloc vandal-resistant 2 wire video pushbutton panel for 8 calls with stainless steel finish. The...



346310

Switchboard for 2 WIRE audio and video systems Allows access to various services (video door entry f...



363915

One-family handsfree kit with Classe 300EOS with Netatmo handsfree connected video internal unit and...



308002

Monobloc vandal-resistant 2 wire video pushbutton panel for 8 calls with aluminium finish. The item ...



344642

Connected 2 wire / Wi-Fi handsfree video internal unit with inductive loop, 7" Touch Screen LC...



336905

Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm2 brown and...