

HEAVY > 1250 N / 5 cm

### Stapa Socket-E-S-v



**Pipelife Steel Conduit (plain) in 3 m lengths as per IEC 614, EN 50086-2-1 for high mechanical loads**

**Designation:** EN 445711 IEC 400

**Material:** St 34 milled soft steel

**Design:** Hot dip galvanised or unenamelled

**Temperature range:** - 45° to + 400° C

**Material Characteristics:** High mechanical strength, limited cold bending

**Application:** Industry installation, interior installation, utility vehicle manufacture.

Can be delivered deburred.

Galvanised design + 2 kg weight increase per bundle

Stapa Steck-E-S-v Type	16	20	25	32	40	50	63
Art.-Nr.	21256516	21256520	21256525	21256532	21256540	21256550	21256563
Outside Ø mm	16	20	25	32	40	50	63
Inside Ø mm	14,0	18,0	22,6	30,6	37,6	47,6	60,6
Weight kg/100 m	37	47	70	91	115	144	182
Bundle contents m	30	30	30	21	15	15	15
Master bundle m	600	600	600	420	150	150	150

#### Stapa-Socket-E-S Bends

90°, made at oversized pipe, with 2 threads and 1 coupler. Can be delivered hot dip galvanised or unenamelled, as well as deburred. Galvanised + 8 % weight increase.

Bends	16	20	25	32	40	50	63
Art.-Nr.	21266516	21266520	21266525	21266532	21266540	21266550	21266563
Pieces per box	15	25	25	20	15	5	3

#### Stapa-Socket-E-S Couplers

Hot dip galvanised or unenamelled. Galvanised + 8 % weight increase.

Couplers	16	20	25	32	40	50	63
Art.-Nr.	21276516	21276520	21276525	21276532	21276540	21276550	21276563
Pieces per box	25	50	50	50	25	10	5

#### Terminal Sleeves

with plastic protection, galvanised.

Terminal Sleeves	16	20	25	32	40	50	63
Art.-Nr.	21286516	21286520	21286525	21286532	21286540	21286550	21286563
Pieces per box	25	50	50	50	25	10	5

#### Clamp, galvanised.

Clamp	16	20	25	32	40	50	63
Art.-Nr.	21288116	21288120	21288125	21288132	21288140	21288150	21288163
Pieces per box	100	100	100	100	50	50	50

