

Air-tight cavity wall installation



LUFTDICHT



O-range ECON® 64 one-gang junction box

- Air-tight design with sealing membranes
- fully-insulated air-tight through-wiring for combinations using support connectors
- tool-free cable or conduit entries
- integrated strain relief of NYM cables, self-locking of conduits
- Art. No. 9264-22 replaces Art. No. 9264-21, Art. No. 9264-78 replaces Art. No. 9264-77

Order number:	9264-22
EAN:	4013456548299
For panel thickness	7 - 40 mm
Depth	62 mm
Cut hole Ø	68 mm
Device screws	2
Tube entries up to M25	2
Cable entries 5 x 2.5 mm ² or 7 x 1.5 mm ²	1
Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ²	3
Cable entries 3 x 1.5 mm ²	3
Support connectors for each package	7
Air-tight	
Packaging inner/dispatch	25/250
Price/100 ST	212.00€
Price group	110

Air-tight O-Range® cavity wall boxes with ECON® technology for energy-efficient electrical installation according to EnEV and for installations under clean-room and hygiene conditions. The elastic ECON® technology sealing membrane allows air-tight electrical installation.

- Elastic sealing membrane for guaranteed air-tightness
- Innovative clamp technology with integrated cable retention
- Tool-free cable and conduit entry
- Air-tight combined with support connector

O-range®

