


Cable Ties Polyamide 6.6 standard T18R



T-Series in PA66 natural, Article number: 111-01929

- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.



Base Data

Application Tool	MK20, MK3PNSP2, MK7P, EVO7, MK3SP
Colour	Natural (NA)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T18R PA66 NA 1000
Product Family	T-Series in PA66 natural
Product Group	Cable Ties Polyamide 6.6 standard
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T18R.NN7P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	22.0 mm
Bundle Ø max. (imperial)	.86 "
Bundle Ø min.	1.5 mm
Bundle Ø min. (imperial)	.06 "
Length (L)	100.0 mm
Length (L) (imperial)	4.0 "
Min. Tensile Strength (lbs)	18 lbs
Min.Tensile Strength (N)	80 N
Width (W)	2.5 mm
Width (W) (imperial)	.10 "

Logisitic and Packaging

Carton Quantity	40000 pcs.
EAN / GTIN	4031026104249
Pack Cont.	1000
Quantity of Europallet	720000 pcs.
Quantity per	pieces
Weight	0.28 kg

Material and Specifications

ELV compliant Dir. Art. 4 (2)	YES
Flammability	UL94 V2
Halogenfree	Yes
Material	PA66
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)

REACH compliant Regu. Art. 33	YES
Specification	UL ZODZ2.E85319, DIN 30015954, GL 86 137-81 HH
UL OCD link	Link
UL-File Number	E85319