

Cable Ties for outdoor use (UV-resistant) T18R

**T-Series in PA66W black, Article number: 111-01960**

- Weather-resistant black cable tie available in a wide range of sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail
- UV-resistant

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.



Catalogue page (February 2014)



All catalogue pages

Base Data

Application Tool	MK20, MK3PNSP2, MK7P, EVO7, MK3SP
Colour	Black (BK)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T18R PA66W BK 100
Product Family	T-Series in PA66W black
Product Group	Cable Ties for outdoor use (UV-resistant)
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T18R.WB3P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	22 mm
Bundle Ø max. (imperial)	.86 "
Bundle Ø min.	1.5 mm
Length (L)	100 mm
Length (L) (imperial)	4.0 "
Min.Tensile Strength (N)	80 N
Thickness (T)	1.0 mm
Width (W)	2.5 mm
Width (W) (imperial)	.10 "

Logistic and Packaging

Carton Quantity	32000 pcs.
EAN / GTIN	4031026104294
Pack Cont.	100
Quantity of Europallet	576000 pcs.
Quantity per	pieces
Weight	0.28 kg

Material and Specifications

ELV compliant Dir. Art. 4 (2)	YES
Flammability	UL94 V2
Halogenfree	Yes
Material	PA66W
Material	Polyamide 6.6 UV Resistant (PA66W)
Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)
REACH compliant Regu. Art. 33	YES

Specification

UL ZODZ2.E85319, DIN 30015954, GL 86 137-81 HH, Det Norske Veritas