


- Made of polyamide in accordance with DIN EN 50085-1 and -2-2 for dry rooms with dry-cleaned floors
  - With carpet frame for 5 or 12 mm flooring thickness
  - Universal mounting kit for installation in junction boxes, trunking systems, double floors or cavity floors
- Minimum installation depth with 5 mm flooring recess: 70 mm
  - Minimum installation depth with 12 mm flooring recess: 77 mm
- Available colours**  
RAL 7011, iron grey  
RAL 9005, deep black
- Material**  
Polyamide



VQ12057011

**Service unit VQ12**

- Properties:**
- For up to 12 installation devices in 3 device casings GTVR400, GBVR400, GTVD300
  - Device casings can be lowered in increments down to 18 mm
  - Including cable holder
  - Outer dimensions: 263 x 263 mm
  - Installation dimensions: 244 x 244 mm




Designation	PU	Order no.
Service unit Q12 f 5mm flooring eg	4	<b>VQ12057011</b>
Service unit Q12 f 5mm flooring ts	4	<b>VQ12059005</b>
Service unit Q12 f 12mm flooring eg	3	<b>VQ12127011</b>
Service unit Q12 f 12mm flooring ts	3	<b>VQ12129005</b>



VEDEQ12P1

**Cover inlay for service unit VQ12**

- Properties:**
- Cover inlay made of cardboard to serve as spacer between cover and flooring
  - Dimensions: 185.3 x 230 mm
  - Material thickness: 1 mm - P1  
2 mm - P2



Designation	PU	Order no.
Cover inlay made of cardboard for VQ12 1mm	300	<b>VEDEQ12P1</b>
Cover inlay made of cardboard for VQ12 2mm	300	<b>VEDEQ12P2</b>