

Surface luminaire with IP54

MODUS KX 4000, 1210mm, LED 840, opal cover, surface, not dimable, 700mA

Code: KX4000M4KO/ND
EAN: 8596099046712



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP54
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	3800
System power (W):	25	Luminaire efficacy (lm/W):	152
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Rozměry

Length (mm):	1210	Width (mm):	110
Height/depth (mm):	60	Built-in length (mm):	1000
Size version:	M	Weight (kg):	2,1

Elektrické vlastnosti

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		