









## SCHUKO socket outlet 16 A 250 V~ with LED orientation light and shutter



Specification	Order No.	Packing unit	PS	EAN
 cream white glossy	1170 01	1/5	02	4010337170013
 pure white glossy	1170 03	1/5	02	4010337170037
 pure white matt	1170 27	1/5	02	4010337170273
 anthracite	1170 28	1/5	02	4010337170280
 colour aluminium	1170 26	1/5	02	4010337170266
 black matt	1170 005	1/5	02	4010337037637
 grey matt	1170 015	1/5	02	4010337082903
 stainless steel (lacquered)	1170 600	1/5	02	4010337021124

## Features

- SCHUKO socket outlet with inserted light strip.
- The white LEDs project a light corridor downwards. This produces indirect orientation light that also avoids bothersome glare in bedrooms.
- The integrated twilight sensor waits until twilight to automatically switch on the LED light and switches it off again when sufficient daylight is detected.
- The LED light is completely integrated in the cover plate, eliminating the need for separate connection.

---

## Technical data

### Power consumption

- |              |                            |
|--------------|----------------------------|
| - Operation: | 0.25 W / 0.35 VA / 1.5 mA  |
| - Standby:   | 0.175 W / 0.25 VA / 1.0 mA |

Light intensity:	0.2 cd
------------------	--------

Installation depth:	32 mm
---------------------	-------

Ambient temperature:	-15 °C to +40 °C
----------------------	------------------

### Connections

- |                        |  |
|------------------------|--|
| - for conductors from: | 1.5 mm <sup>2</sup> to 2.5 mm <sup>2</sup> |
|------------------------|--|

---

## Notes

- Increased contact protection (Safety Plus) pursuant to IEC 60884-1.
-