

SWITCHING POWER SUPPLIES

Mean Well Switching Power Supplies Constant Current Multi



Image title

Multifunctional constant current power supplies with selectable output current level by DIP switch. Dimmable by 0-10 V or DALI / PUSH-DIM. Dimmable by 0-10 V, DALI / PUSH-DIM or KNX. Noiseless – without fan.

MEAN WELL SWITCHING POWER SUPPLIES General Manual

165.7 KB 

TECHNICAL DATA

Power source:	180–290 VAC + 260–400 VDC
Frequency range:	47–63 Hz
Dimensions (l x w x h):	105 x 68 x 23 mm (25 Watt) 124 x 82 x 23 mm (40 + 60 Watt)
Weight:	0,16 kg (25 Watt) 0,24 kg (40 + 60 Watt)

25 WATT*

350 mA	6–54 V
500 mA	6–50 V
600 mA	6–42 V
700 mA	6–36 V

900 mA	6–28 V
1050 mA	6–24 V
*at 350 mA 18 Watt	

40 WATT

350 mA	2–100 V
500 mA	2–80 V
600 mA	2–67 V
700 mA	2–57 V
900 mA	2–45 V
1050 mA	2–40 V

60 WATT

500 mA	2–90 V
600 mA	2–90 V
700 mA	2–86 V
900 mA	2–67 V
1050 mA	2–57 V
1400 mA	2–42 V

PRODUCT TYPES

order code	description	MM	dimmable	
L50LCM02A	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 25 Watt*, 1-10 V	yes	0-10 V	
L50LCM04A	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 40 Watt, 1-10 V	yes	0-10 V	
L50LCM06A	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 60 Watt, 1-10 V	yes	0-10 V	
L50LCM02D	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 25 Watt*, DALI	yes	DALI	
L50LCM04D	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 40 Watt, DALI	yes	DALI	
L50LCM06D	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 60 Watt, DALI	yes	DALI	
L50LCM04K	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 40 Watt, KNX	yes	KNX	
L50LCM06K	SWITCHING POWER SUPPLY CONSTANT CURRENT MULTI 60 Watt, KNX	yes	KNX	

*at 350 mA 18 Watt



Member of PROLED GROUP