

SWITCHING POWER SUPPLIES

Mean Well Switching Power Supplies Constant Current Dimmable



Power supplies can be dimmed with standard AC phase-cut dimmers (triac). Noiseless – without fan.

MEAN WELL SWITCHING POWER SUPPLIES General Manual

165.7 KB 

TECHNICAL DATA

Frequency range: 47–63 Hz

PRODUCT TYPES

order code	output current	output voltage	power	MM	power source	dimensions (l x w x h)	weight	
L503501CD	350 mA	24-48 VDC	16,8 Watt	–	180-295 VAC	84 x 57 x 30 mm	0,2 kg	
L503502CD	350 mA	40-58 VDC	20,3 Watt	–	180-295 VAC	84 x 57 x 30 mm	0,2 kg	
L507001CD	700 mA	16-24 VDC	16,8 Watt	–	180-295 VAC	84 x 57 x 30 mm	0,2 kg	
L507002CD	700 mA	24-36 VDC	25,2 Watt	–	180-295 VAC	84 x 57 x 30 mm	0,2 kg	
L507004CD	700 mA	34-57 VDC	40,0 Watt	yes	180-295 VAC	128 x 60 x 32 mm	0,2 kg	
L501001CD	1050 mA	12-16 VDC	16,8 Watt	–	180-295 VAC	84 x 57 x 30 mm	0,2 kg	
L501002CD	1050 mA	16-24 VDC	25,2 Watt	–	180-295 VAC	84 x 57 x 30 mm	0,2 kg	
L501004CD	1050 mA	22-38 VDC	40,0 Watt	yes	180-295 VAC	128 x 60 x 32 mm	0,2 kg	

order code	output current	output voltage	power	MM	power source	dimensions (l x w x h)	weight	
L501006CD	1050 mA	34-57 VDC	60,0 Watt	yes	180-295 VAC	128 x 60 x 32 mm	0,4 kg	
L501404CD	1400 mA	22-38 VDC	40,0 Watt	yes	180-295 VAC	128 x 60 x 32 mm	0,2 kg	
L501406CD	1400 mA	25-43 VDC	60,0 Watt	yes	180-295 VAC	128 x 60 x 32 mm	0,4 kg	

© MBN GmbH



Member of PROLED GROUP