

# SPOT LIGHTS

## Spot Light IP65 1x 2 Watt Mono



The PROLED SPOT LIGHT IP65 is suitable for emphasis lighting indoors as well as outdoors. Combined with a ground spike it is also perfect for plant and garden lighting.

- dimmable and controllable via DMX 512, DALI, KNX, 1-10 V, CASAMBI, RF by MULTI power supplies or PRO CONTROLLER

> EULUMDAT/IES information

### TECHNICAL DATA

IP classification:	IP65 (for outdoor use)
Power source:	24 VDC
Housing:	silver anodized aluminium or powder coated aluminium black (RAL 9011)
Electrical connection:	1x cable 2 m H05RN-F 2x 1,0 mm² with 2-PIN IP68 connector male
Average lifetime:	50.000 h at L80/B10
Operating temperature range:	-10° C till +45° C

### PHOTOMETRIC DATA







LED type:	OSRAM 2 Watt high power
Luminous flux:	white 200 Lumen warm white 180 Lumen
Colour temperature:	white 6500 K warm white 3000 K
CRI:	80

Beam angle:

15° (only white) and 30°


Due to conditions of production photometric data can vary from production batch to production batch within the EU directive.

PRODUCT TYPES

order code	colour	housing	beam angle	LED pcs	LED power	power consumption*	weight	EEL	
L173141	white	silver	15°	1	2 Watt	2,5 Watt	0,4 kg	A++	
L173141B	white	black	15°	1	2 Watt	2,5 Watt	0,4 kg	A++	
L173143	white	silver	30°	1	2 Watt	2,5 Watt	0,4 kg	A++	
L173143B	white	black	30°	1	2 Watt	2,5 Watt	0,4 kg	A++	
L173163	warm white	silver	30°	1	2 Watt	2,5 Watt	0,4 kg	A+	
L173163B	warm white	black	30°	1	2 Watt	2,5 Watt	0,4 kg	A+	

\*Actual power consumption

ACCESSORIES

product description									
	Ground spike for SPOT LIGHT 1x 3 Watt								»

© MBN GmbH

PROLED®

Member of PROLED GROUP