

UniCam® Connector, LC

single-mode (OS2), APC

CORNING

Corning UniCam® LC connectors offer optical performance in a fast, easy field-termination solution ideal for fibre-to-the-workstation applications where setup and teardown time is critical. The high-precision mechanical splice technology enables fibre optic networks to be installed quickly and cost effectively. Installation of an LC, SC or ST® compatible connector can be accomplished in about 50 seconds to one minute with the UniCam High-Performance Tool Kit. The lightweight, handheld installation tool and high-performance precision cleaver virtually eliminate human variability during installation, ensuring terminations are right the first time, every time. This kit was designed with consideration for network installers, from the cleaver, with its intuitive, hand-held precision design and dual-clamp precision hold, to the installation tool, with its immediate go/no-go feedback signal indicating proper mating of the field fibre to the fibre stub. Installation is as easy as strip, clean, cleave, cam and crimp, with exceptional optical performance assured. Every UniCam connector is assured to meet the published specification at the time of installation or Corning will replace it.

Corning UniCam® high-performance connectors offer best-in-class optical performance in a fast, easy field-termination solution. These high-precision zirconia ceramic ferrule connectors assured exceptional insertion loss – 0.1 dB typical/0.5 dB maximum per connector pair for multimode, 0.2 dB typical/0.5 dB maximum per connector pair for single-mode. Installation of an LC, SC or ST® compatible connector can be accomplished in about 50 seconds to one minute with the UniCam high-performance tool kit.

The lightweight, handheld installation tool and high-performance precision cleaver virtually eliminate human variability during installation, ensuring terminations are right the first time, every time. This kit was designed with consideration for network installers, from the cleaver, with its intuitive, hand-held precision design and dual-clamp precision hold, to the installation tool, with its immediate go/no-go feedback signal indicating proper mating of the field fibre to the fibre stub. Installation is as easy as strip, clean, cleave, cam and crimp, with exceptional optical performance assured. Every UniCam® connector is assured to meet the published specification at the time of installation or Corning will replace it.

Features and Benefits

Performance guarantee

100 percent yield guarantee



Part Number: 95-200-94

UniCam® Connector, LC

single-mode (OS2), APC

CORNING

Features and Benefits

Broad operating temperature (-40° to +75°C)

Utility and flexibility

Factory-polished end face

Consistent optical performance

Fast termination and no consumables

Low installation cost

Minimum insertion loss

Optimum optical performance

Standards

Approvals and Listings Passed EIA/TIA 568-B.3

Intermateability Connectors are FOCIS compliant with TIA/EIA 604-10A and IEC61754-20

Specifications

General Specifications

| | |
|----------------|------------------------------|
| Technology | No-Epoxy/No-Polish |
| Keyed | No |
| Product type | Field-Installable Connectors |
| Corning Logo | Yes |
| Packaging | Single Pack |
| Fibre Category | single-mode (OS2) |

Temperature Range

| | |
|-----------|--|
| Operation | -40 °C to 75 °C exceeding EIA/TIA 568-B.3 (-40 °F to 167 °F exceeding EIA/TIA 568-B.3) |
|-----------|--|

Design - Connector

| | |
|------------------|-----------|
| Connector Type | LC APC |
| Ferrule Material | Ceramic |
| Housing material | Composite |

UniCam® Connector, LC

single-mode (OS2), APC

CORNING

Design - Connector

| | |
|----------------|-------|
| Housing Colour | green |
| Boot colour | green |

Mechanical Specifications - Connector

| | |
|------------------------------|---|
| Durability | ≤ 0.2 dB change by 500 rematings, FOTP-21 |
| Temperature cycling | ≤ 0.3 dB IL, -40° to +75°C, 21 cycles |
| Nominal fibre outer diameter | 125 µm |

Optical Specifications - Connector

| | |
|-------------------------|--|
| Reflectance | ≤ -60 dB (-0°C to +60°C = -40 dB (FBC-007, for 900 µm) ; 10-25°C = -60 dB (FBC-007, for 900 µm)) |
| Insertion loss, typical | 0.4 dB |
| Insertion Loss, Maximum | 0.75 dB |
| Polish | APC |

Chemical Characteristics

| | |
|------|---|
| RoHS | Free of hazardous substances according to RoHS 2002/95/EG |
|------|---|

Ordering Information

| | |
|---------------------|--|
| Part Number | 95-200-94 |
| Product Description | UniCam® High-Performance Connector, LC APC, single-mode (OS2), ceramic ferrule, logo, single pack, green housing, green boot |
| EAN Code | 4056418171111 |

Shipping Information

| | |
|--------------------|---|
| Units Per Delivery | 1/1 |
| Package Contents | Connector, trigger, crimp band, boot (900 µm), boot (3.0 mm), boot (2.0 mm) |

UniCam® Connector, LC

single-mode (OS2), APC

The Corning logo consists of a solid blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

CORNING

Notes



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.

CORNING