


RF/TP media coupler or RF repeater for KNX



Specification	Order No.	Packing unit	PS	EAN
	5110 00	1/5	06	4010337017264

With the KNX RF system devices, the RF pushbutton sensors for KNX and RF hand-held transmitters for KNX are incorporated and parameterised in the KNX structure via the ETS.

Features

- Interface between wired KNX products (TP) and KNX RF wireless products.
- Configurable as a media coupler or repeater via the ETS.
- Can be used as segment coupler for start-up with ETS from Version 6.0.5 (index status from I02).
- Devices can be updated. Firmware updates (e.g. I00 to I01) can be performed with ease via the ETS Service App.
- Supports KNX Data Secure communication (KNX Data Secure telegrams can be processed and filtered, forwarded or blocked according to the settings).
- Fast communication between KNX products in main line and line (long frame support with ETS5 and higher).

Technical data

KNX medium:	RF1.R, TP1-256
Start-up mode:	S mode
Rated voltage:	
Ambient temperature:	-20 °C to +45 °C
Wireless frequency:	868.3 MHz
Transmission power:	max. 20 mW
Range (free field):	approx. 100 m

Notes

- KNX Data Secure compatible.
-

Scope of supply

- Connection and junction terminal for KNX included in the scope of supply.
-