

eNet wireless universal transmitter, 2-gang Mini



| Specification | Order No. | Packing unit | PS | EAN |
|---------------|-----------|--------------|----|---------------|
| | 5453 00 | 1/5 | 42 | 4010337774310 |

Features

- The eNet wireless transmitters transfer switching, dimming, and blind adjustment commands to corresponding eNet wireless receivers.
- The eNet wireless universal transmitter enables the transmission of switching, dimming or blind commands to suitable eNet wireless receivers.
- Installation in device box, surface-mounted housing, or in an installation adapter.
- Detection of voltage levels and changes at input.
- Connection of an external status LED.
- Indication of transmission status.
- Operating modes: 1-gang switching/dimming/blind, 1-gang automatic function, 2-gang switching/dimming/button operation, 2-gang automatic function.

Can be set with eNet server:

- Fully encrypted wireless transmission (AES CCM) from eNet Server software version 2.0.
- 2-gang blind.
- Operation locks.
- Establishing connections, enabled or disabled.
- Status for forced setting.
- All-On or All-Off scenes, threshold value scenes, and individual scenes can be configured.
- Configuration of scene button via eNet SMART HOME App (if-then rules) to trigger actions, scenes, or timers.
- Repeater function.
- Device software update.
- Localisation of the device.

Technical data

| | |
|----------------------|-----------------------------|
| Ambient temperature: | -5 °C to +45 °C |
| Wireless frequency: | 868.3 MHz |
| Range (free field): | approx. 100 m |
| Rated voltage: | AC 110 V to 230 V, 50/60 Hz |
| Standby: | 0.5 W |
| Inputs | |
| - Cable length: | max. 100 m |

Illustrations are similar and may deviate from originals.

| | |
|--------------------|-------------------|
| - Input current: | 2 mA |
| - Signal duration: | min. 200 ms |
| Output status LED | |
| - Rated voltage: | AC 110 V to 230 V |
| - Output current: | 40 mA |

Notes

- Wireless approval is valid for EU and EFTA countries.

Dimensions in mm

Ø 53 H 23
