




**SCHUKO socket outlet 16 A 250 V~ with shutter and USB power supply, 2-gang
Type A / type C**



Specification	Order No.	Packing unit	PS	EAN
cream white glossy	2459 01	1	02	4010337076223
 pure white glossy	2459 03	1	02	4010337076179
 pure white matt	2459 27	1	02	4010337076186
 anthracite	2459 28	1	02	4010337076285
colour aluminium	2459 26	1	02	4010337076193
black matt	2459 005	1	02	4010337076209
grey matt	2459 015	1	02	4010337090151
stainless steel (lacquered)	2459 600	1	02	4010337076148

Features

- Power supply with integrated plug connector USB type A.
- Up to two end devices can be charged simultaneously.

Technical data

Input voltage: AC 220 - 250 V, 50/60 Hz

USB connection: 1 x type A, 1 x type C

Output voltage USB: DC 5 V

Charging current

- USB A: Max. 2.4 A

- USB C: Max. 3 A

Standby: ≤80 mW

Connections

- for conductors from: 1.5 mm² to 2.5 mm²

Installation depth: 31 mm

Ambient temperature: +5° C to +35° C

Notes

- Increased contact protection (Safety Plus) pursuant to IEC 60884-1.
- During long charging cycles, the housing of the product may heat up.
- Using a deep device box is recommended.

Scope of supply

- Type A or type C USB cables are not included in the scope of delivery.