




Surface-mounted door station, 1-gang



Specification	Order No.	Packing unit	PS	EAN
 pure white	1266 66	1	18	4010337266662
 anthracite	1266 67	1	18	4010337266679
 colour aluminium	1266 65	1	18	4010337266655

Features

- Fully pre-assembled surface-mounted door station for vertical surface-mounted installation. This allows quick and clean installation.
- In the design of the design line Gira TX_44.
- Torsionally rigid surface-mounted housing thanks to aluminium profile.
- Frame made of shatter-proof thermoplastic with high resistance to ultraviolet light as well as a scratch-resistant, care-free surface.
- Theft protection by means of screws with hexalobular socket.
- Signal transmission and supply of the audio and video components via reverse-polarity-protected and short-circuit-proof 2-wire bus.
- One-man start-up with easy start-up procedure.
- Weather-resistant speaker.
- High-quality electret microphone.
- Speakerphone function (voice-controlled talk-back with echo and background noise suppression).
- Acknowledgement tone when call button is pressed.
- Adjustable voice volume.
- White call-button illumination in LED technology. Even, clearly visible call button illumination is achieved via maintenance-free, energy-saving LED technology.
- Sprayed-water proof call-button cover plate made of shock-resistant plastic.
- Name plate of the call button can be exchanged without tools and without frame disassembly.
- Professional labelling is available from the Gira Inscription Service www.marking.gira.com or using the Gira inscription software.
- Low profile height of just 19 mm.

Technical data

Power supply:	via the 2-wire bus
Connections	
- 2-wire bus:	2x screw terminals

- Additional power supply: 2x screw terminals

Protection type: IP44

Ambient temperature: -25 °C to +70 °C

Dimensions in mm

Door station, 1-gang:	W 110	H 181	D 19
Name plate:	W 62	H 62	D -
