Distributed by BTicino



## **GENERAL CATALOGUE**



# NT4362

#### blicino

Reading lamp dimmable - installing the head of the bed allowing you to have a directional light. It is equipped with a flexible arm (lenght 31 cm) that allows you to orient the illuminating ends. The light intensity can be dimmed by pressing and holding the On / Off integrated command. It can also be connected to a remote control and, if necessary, you can disable the built-in command with a 30 sec pressure -LED light - Consumption 3W - Luminous Flux 110 lumens (equivalent to 15W incandescent) - Duration 40.000 hours - 1 module (recessed) - Tech

Technical features		Commercial data	
1 - Brand	BTicino	Minimum quantity	1
9 - Series	Livinglight	Sales unit	1
15 - Modules	1	EAN code	8005543537190
17 - Rated power (W)	3W		
18 - Rated voltage	230Vac		

#### **Technical documentation**

### ↓ Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.