


Pate	
Customer	
Project	
уре	

Doze Round Wall Recessed 80 1x LED 2700K Trailing Edge White Structure



Doze Round is a circular luminaire perfect for showing the way along a hallway or staircase. A stout rim in white or black and a polycarbonate diffuser make its designs simple, yet effective. What's also great about it, is that Doze Round fits into a standard electrical junction box (included), found in most modern buildings. A performant alternative for a standard recessed spot.





Spec	ifica.	tions

Material	12330009
Light Source Type	LED
LED Type	ACRICHE
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Input Voltage	230V
Luminaire power (W)	5.2
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Recessed
Cut-out size (mm)	ø68
Mounting depth (mm)	47.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	205.0
Delivered lumens (Im)	194
Efficacy (Im/W)	43
Glare rating	28




TM30 & CRI diagram







Installation Accessories



12339930 Conbox Ø130x135

Choose a required accessory