

Product Code 55-1574-14-00 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Step Square

Signalling Step Square 3.8 LED warm-white 3000K CRI 80 PHASE CUT White IP20 67lm

Technical features

Luminaire total power: 3.8W

Real lumens: 67 Real Im/W: 18

Correlated Colour Temperature (CCT): LED warm-white 3000K

Lens / reflector angle: FLOOD 50°

UGR: <=16

Structure material: Aluminium

Structure finish: White

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: PHASE CUT

Power Factor: 1.00

Useful life: 50,000h L80B20

Warranty: 5 años

Easily recyclable luminaire













Luminotechnic features

CRI: 80

MacAdam steps: 3

Photobiological risk: RG1

UGR crosswise: 0.1 UGR lengthwise: 0.1

Lampholder	Quantity	Light source power (W)
LFD	1	3.8W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 55-1574-14-00

Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Step Square

Signalling Step Square 3.8 LED warm-white 3000K CRI 80 PHASE CUT White IP20 67Im

Logistics

x 50

Net weight (kg): 0.15

Packaged weight (kg): 0.24

Packaging: 80mm x 80mm x 95mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 55-1574-14-00

Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Step Square

Signalling Step Square 3.8 LED warm-white 3000K CRI 80 PHASE CUT White IP20 67lm

Accessories included



Recess case

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.