



Exit

EXIT DF20M CT SA LF

Escape sign luminaire with a visibility range of 20 metres.

Control system CT

Order code 4380

EAN 8002219730442

Technical specifications

Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Absorbed SE (max)	4 W
Control system	CT
Autonomy	1h, 1.5h, 2h, 3h, 8h
Battery included	Yes
Battery type	LiFe
Battery	LiFe 6.4V 0.6Ah
Charging time	12 h
Autonomy test time	60 min
Autonomy test frequency	182 days
Test frequency	28 days
Ambient temperature (min)	-10 °C
Ambient temperature (max)	45 °C
Insulation class	II
LED number	24
CRI color rendering	>80
Operation mode	NM/M
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.53
Glow wire strength	850 °C - 30s.
Light sensor	Yes
Movement sensor	Yes
Number of Batteries	1
Pictogram included	Yes
Rest mode	Yes
Visibility distance	20 m
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V

Installation and applications

Environment	Offices
Application	Offices, Safety Sign, Public Areas, Shops

Mechanical specifications

Height	30 mm
Length	314 mm
Width	194 mm



Weight	0.5 Kg
Body material	Polycarbonate
Colour housing	White RAL 9003
Cover material	PMMA transparent thermoplastic
Protection grade IP	IP40
Protection grade IK	IK05

Certifications and norms

UK SI 2021 No. 1095, EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 61547:2009, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN 60598-2-22:2014 + AC:2015 + AC:2016-05 + AC:2016-09 + A1:2020, EN IEC 63000:2018, EN 62493:2010

Accessories



4312
ACCESS INC CONT UP LED EXIT
20M



4319
KIT BINARIO TRIFASE UP LED



15036
MODULO LG



4316
SOSPEN TIGES L500



15038
MODULO DALI



14771
SOSPENSIONE MONO/BI
LAMPADA



4315
SOSPEN TIGES L250



15037
MODULO LGFM



4317
SOSPEN TIGES L1000

Spare parts



415466001
LiFe 6.4V 0.6AH 14500 PACK T