

## Mean Well Dali Switching Power Supplies IP67





Dimmable DALI power supplies with IP classification IP67. For indoor and outdoor use.

Noiseless – without fan.

[PROLED SWITCHING POWER SUPPLIES GENERAL MANUAL \(187.4 KB\)](#)

[5 YEARS WARRANTY INFORMATION](#)

TECHNICAL DATA

|                 |          |
|-----------------|----------|
| Frequency range | 47-63 Hz |
|-----------------|----------|

PRODUCT TYPES

| order code | model | output voltage | power   | MM  | power source                 | dimensions (l x w x h) | weight  |
|------------|-------|----------------|---------|-----|------------------------------|------------------------|---------|
| L502407RD  | DALI  | 24 VDC         | 75 Watt | yes | 100-300 VAC<br>+ 145-400 VDC | 180 x 63 x 36 mm       | 0,80 kg |

| order code | model | output<br>voltage | power       | MM  | power<br>source                 | dimensions (l<br>x w x h) | weight     |
|------------|-------|-------------------|-------------|-----|---------------------------------|---------------------------|------------|
| L502409RD  | DALI  | 24 VDC            | 96<br>Watt  | yes | 100-300 VAC<br>+ 145-400<br>VDC | 199 x 63 x 36<br>mm       | 0,85<br>kg |
| L502415RD  | DALI  | 24 VDC            | 150<br>Watt | yes | 100-300 VAC<br>+ 145-400<br>VDC | 219 x 63 x 36<br>mm       | 0,95<br>kg |
| L502424RD  | DALI  | 24 VDC            | 240<br>Watt | yes | 100-300 VAC<br>+ 145-400<br>VDC | 244 x 71 x 38<br>mm       | 1,22<br>kg |

MEMBER OF THE PROLED GROUP