

Mean Well Switching Power Supplies



Power supplies* for integration in housings or distribution boxes.

MEAN WELL SWITCHING POWER SUPPLIES GENERAL MANUAL (165.7 KB)

TECHNICAL DATA

Frequency range	47-63 Hz
-----------------	----------

PRODUCT TYPES

order code	output voltage	power	fan	power source	dimensions (l x w x h)	weight
L500510	5 VDC	80 Watt	-	90-260 VAC + 125-370 VDC	159 x 97 x 38 mm	0,7 kg
L501201	12 VDC	15 Watt	-	90-260 VAC + 125-370 VDC	63 x 51 x 28 mm	0,1 kg
L501210	12 VDC	100 Watt	-	90-260 VAC + 125-370 VDC	159 x 97 x 38 mm	0,7 kg
L501220	12 VDC	200 Watt	yes	90-260 VAC + 125-370 VDC	199 x 99 x 50 mm	0,9 kg
L501220S	12 VDC - Silent	200 Watt	-	90-260 VAC + 125-370 VDC	199 x 98 x 38 mm	0,8 kg
L501232	12 VDC	320 Watt	yes	90-260 VAC	215 x 115 x 30 mm	0,9 kg
L502406	24 VDC	70 Watt	-	90-260 VAC + 125-370 VDC	129 x 97 x 38 mm	0,5 kg
L502410	24 VDC	100 Watt	-	90-260 VAC + 125-370 VDC	159 x 97 x 38 mm	0,7 kg
L502420	24 VDC	200 Watt	-	90-260 VAC + 125-370 VDC	215 x 115 x 30 mm	0,7 kg
L502432	24 VDC	320 Watt	yes	90-260 VAC	215 x 115 x 30 mm	0,9 kg

order code	output voltage	power	fan	power source	dimensions (l x w x h)	weight
L5048101	48 VDC	100	-	90-260 VAC +	179 x 99 x 30 mm	0,5
		Watt		125-370 VDC		kg
L504820	48 VDC	200	-	90-260 VAC +	215 x 115 x 30	0,7
		Watt		125-370 VDC	mm	kg
L5048321	48 VDC	320	yes	90-260 VAC +	215 x 115 x 30	0,9
		Watt		125-370 VDC	mm	kg

*The MEAN WELL integration power supplies do not comply with EN61000-3-2 Class C.

MEMBER OF THE PROLED GROUP