

PROLED[®]

RF RGBW Remote Controller Wall





The PROLED RF RGBW wall remote controller is a RGBW touch controller with sensitive glass touch panel, designed for wall mounting. It controls in combination with the **RF PWM DIMMER 4-CHANNEL / RF PWM DIMMER IP65 4-CHANNEL** RGB and RGBW luminaires without intensive installation work. The wall remote controller is equipped with an additional DMX 512 output. Dálkový ovladač na stěně má navíc výstup DMX 512.

- 4-channel control via RF (RGBW, RGBA or RGB)
- selection of the desired colour with a colour wheel
- selection of a preprogrammed colour gradient (10 programs)
- dimming of the desired colour or colour gradient
- speed adjustment
- each 4 channels separately dimmable
- Enable to control 4 zones separately.
- each zone can be connected to endless RF PWM DIMMERS
- each RF PWM DIMMER can be controlled by max. 8 RF remote controllers
- 868 MHz
- additional DMX 512 output
- dodatečný výstup DMX 512

PROLED RF RGBW REMOTE CONTROLLER WALL MANUAL (651.2 KB)

5 YEARS WARRANTY INFORMATION

TECHNICAL DATA

Power source

12–24 V (not included)

Operating temperature range	-10° C till +45° C
-----------------------------	--------------------

Dimension (w x d x h)	86 x 12 x 86 mm (depth incl. terminal block 31 mm)
-----------------------	---

Weight	0,13 kg
--------	---------

PRODUCT TYPES

order code	description
------------	-------------

L513180	RF RGBW REMOTE CONTROLLER WALL
---------	--------------------------------

MEMBER OF THE PROLED GROUP