

## Switching Power Supplies Constant Current



Constant current power supplies with MM-sign and F-sign. Can be mounted on inflammable subsurface. Noiseless – without fan.

[PROLED SWITCHING POWER SUPPLIES GENERAL MANUAL \(187.4 KB\)](#)

[5 YEARS WARRANTY INFORMATION](#)

# TECHNICAL DATA

|                 |          |
|-----------------|----------|
| Frequency range | 50/60 Hz |
|-----------------|----------|

## PRODUCT TYPES

| order code | output current | output voltage | power | MM  | power source | dimensions (l x w x h) | weight |
|------------|----------------|----------------|-------|-----|--------------|------------------------|--------|
| L5233012   | 300 mA         | 2-40           | 12    | yes | 220-         | 98 x 39 x 22           | 0,05   |
|            |                | VDC            | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L52335062G | 350 mA         | 9-18           | 6     | yes | 220-         | 81 x 39 x 22           | 0,06   |
|            |                | VDC            | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L52335122G | 350 mA         | 2-34           | 12    | yes | 220-         | 98 x 39 x 22           | 0,06   |
|            |                | VDC            | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L52335202G | 350 mA         | 2-58           | 20    | yes | 220-         | 113 x 44 x 28          | 0,10   |
|            |                | VDC            | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L5235003   | 500 mA         | 2-6 VDC        | 3     | yes | 220-         | 81 x 39 x 22           | 0,05   |
|            |                |                | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L52350062G | 500 mA         | 6-12           | 6     | yes | 220-         | 81 x 39 x 22           | 0,06   |
|            |                | VDC            | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L52350202G | 500 mA         | 2-40           | 20    | yes | 220-         | 113 x 44 x 28          | 0,10   |
|            |                | VDC            | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |
| L52370062G | 700 mA         | 6-9 VDC        | 6     | yes | 220-         | 81 x 39 x 22           | 0,05   |
|            |                |                | Watt  |     | 240          | mm                     | kg     |
|            |                |                |       |     | VAC          |                        |        |

| order code        | output<br>current | output<br>voltage | power | MM  | power<br>source | dimensions (l<br>x w x h) | weight |
|-------------------|-------------------|-------------------|-------|-----|-----------------|---------------------------|--------|
| <b>L52370122G</b> | 700 mA            | 2-17              | 12    | yes | 220-            | 98 x 39 x 22              | 0,06   |
|                   |                   | VDC               | Watt  |     | 240             | mm                        | kg     |
|                   |                   |                   |       |     | VAC             |                           |        |
| <b>L52370202G</b> | 700 mA            | 2-29              | 20    | yes | 220-            | 113 x 44 x 28             | 0,10   |
|                   |                   | VDC               | Watt  |     | 240             | mm                        | kg     |
|                   |                   |                   |       |     | VAC             |                           |        |
| <b>L5231006</b>   | 1050<br>mA        | 2-4 VDC           | 6     | yes | 220-            | 98 x 39 x 22              | 0,06   |
|                   |                   |                   | Watt  |     | 240             | mm                        | kg     |
|                   |                   |                   |       |     | VAC             |                           |        |
| <b>L5231017</b>   | 1050<br>mA        | 2-16              | 17    | yes | 220-            | 113 x 44 x 28             | 0,10   |
|                   |                   | VDC               | Watt  |     | 240             | mm                        | kg     |
|                   |                   |                   |       |     | VAC             |                           |        |
| <b>L52310202G</b> | 1050<br>mA        | 2-19              | 20    | yes | 220-            | 113 x 44 x 28             | 0,10   |
|                   |                   | VDC               | Watt  |     | 240             | mm                        | kg     |
|                   |                   |                   |       |     | VAC             |                           |        |
| <b>L5231260</b>   | 1200<br>mA        | 25-50             | 60    | yes | 100-            | 184 x 61 x 32             | 0,30   |
|                   |                   | VDC               | Watt  |     | 240             | mm                        | kg     |
|                   |                   |                   |       |     | VAC             |                           |        |

MEMBER OF THE PROLED GROUP