



RF PWM Dimmer 4-Channel



The PROLED RF PWM DIMMER 4-CHANNEL is the receiver for the RF remote controllers and RF remote push buttons.

RF RGBW1 REMOTE CONTROLLER

RF RGBW2 REMOTE CONTROLLER

RF DW REMOTE CONTROLLER

RF MONO REMOTE CONTROLLER

RF MONO REMOTE CONTROLLER STYLE

RF DW MINI REMOTE CONTROLLER

RF MONO CONVERTER

RF MONO REMOTE PUSH BUTTON

RF RGBW REMOTE CONTROLLER WALL

RF DW REMOTE CONTROLLER WALL

RF MONO REMOTE CONTROLLER WALL

With the RF PWM DIMMER monochrome LED luminaires, Dynamic White and RGB/RGBA/RGBW applications can be controlled. The output voltage corresponds to the supply voltage of 12–48 V. CA (Common Anode – common plus).

PROLED RF PWM DIMMER 4-CHANNEL MANUAL (4.1 MB)

5 YEARS WARRANTY INFORMATION

TECHNICAL DATA

Power Range	12–48 V
Output	to 24 VDC: 4x 5 A 48 VDC: 4x 2,5 A
Control signal	RF 868 MHz
Output channels	4
Output voltage	12–48 VDC
Operating temperature range	-10° C till +45° C
Dimensions (l x w x h)	167 x 55 x 24 mm

Weight	0,12 kg
--------	---------

PRODUCT TYPES

order code	description
L513170	RF PWM DIMMER 4-CHANNEL

MEMBER OF THE PROLED GROUP