

# Frame Mini



## Frame Mini Black 550lm 3000K Ra>80 Trailing edge dimming

Article code: 605451  
EAN: 7021986054514



### Electrical

System wattage: 6.5W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 125, B16: 200

### Light technic

Type of light source: LED  
Luminous flux: 550lm  
Efficacy: 85 lm/W  
Colour temperature: 3000K  
Colour rendering (CRI): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L70/B20>100,000  
Lifetime: L80/B20>75,000  
Light distribution: Direct  
Optic: Opal  
Beam angle: 110°  
Photobiological safety: RG 0

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class II  
Fire protection class: 850°C - 30s

### Energy and approvals

Contains light source of energy class: E  
Breeam: Fulfils Hea 01 for flicker free lighting  
BVB: Yes

### Materials and finish

Housing: Aluminium  
Colour: Black (RAL 9004)  
Optics: UV-stabilized polycarbonate

### Mounting/Connection

Mounting: Surface, Indoor / Outdoor  
Connection: Screwless terminal block

### Dimensions

Length (mm) L: 240  
Width (mm) W: 150  
Height (mm) H: 77  
Weight (kg) gross/net: 1.9 / 1.75

### Packaging

Packing dimensions (mm): 248 x 158 x 92

