

Prelude



Prelude White 1060lm 3000K Ra>90 Trailing edge dimming

Article code: 111345
EAN: 7021981113452



Electrical

System wattage: 14W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 23, B16: 37, C10: 29, C16: 46

Light technic

Type of light source: LED
Luminous flux: 1060lm
Efficacy: 76 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L70/B10>50,000
Light distribution: Direct
Optic: Opal
UGR: UGR<25
Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Aluminium
Colour: Matte white (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Surface, Indoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 510
Width (mm) W: 70
Height (mm) H: 80
Depth (D): 80
Weight (kg) gross/net: 0.842 / 0.82

Packaging

Packing dimensions (mm): 520 x 90 x 80



7 0 2 1 9 8 1 1 1 3 4 5 2