

Frame Mini



Frame Mini White 550lm 3000K Ra>80 Trailing edge dimming

Article code: 605441
EAN: 7021986054415




Electrical

System wattage: 6.5W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 125, B16: 200

Light technic

Type of light source: LED
Luminous flux: 550lm
Efficacy: 85 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B20>100,000
Lifetime: L80/B20>75,000
Light distribution: Direct
Optic: Opal
Beam angle: 110°
Photobiological safety: RG 0



Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Aluminium
Colour: White
Optics: UV-stabilized polycarbonate

Mounting/Connection


Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 240
Width (mm) W: 150
Height (mm) H: 77
Weight (kg) gross/net: 1.9 / 1.75

Packaging

Packing dimensions (mm): 248 x 158 x 92



7 0 2 1 9 8 6 0 5 4 4 1 5